



**HEAT EXCHANGER AND SPACE UNIT
COOLMOBILE 220**

COOLMOBILE 220

This unit works with a standard 230V power supply and can be easily installed by any user. With its compact design, the COOLMOBILE 220 is easy to manoeuvre in small spaces and through narrow passages.

WORKING PRINCIPAL

- The robust construction is very suitable for rental purposes
- Allows the room temperature to be reduced with 10°C
- Easy to install within a few minutes without a specialist
- The extendable connecting leads allow the operation of spaces up to 30 meters
- The cables can be easily connected with quick-release couplings

FEATURES

- 3-stage fan control
- Hour counter
- Built-in thermostat
- Replaceable air filters
- Switch for cooling and ventilation operation

APPLICATIONS

With its high airflow, the COOLMOBILE 220 is ideal for cooling rooms up to 130 m³.

- Tents, large offices
- Trade fairs and restaurants
- Server rooms
- Exhibitions

TECHNICAL SPECIFICATIONS | DIMENSIONS AND WEIGHTS

1 kW = 860 kcal/hr 1 kW = 3,413 Btu/hr 1 kW = 3.6 MJ/hr 1 kg = 1.2 l/hr

COOLMOBILE 220

Productnumber	56.220.000
Cooling capacity / Kw	6,7
Airflow / m ³ / hr	1.500
Connection / V / Hz	230 / 50
Starting current A	13
Power consumption / Kw	2,7
Max. Static pressure / bar	6
ΔT (°C)	10-35
Decibel dB (A) 3mtr distance	49
Dimensions (L x W x H) Heat exchanger / mm	815 x 360 x 1200
Weight / Kg	86
Dimensions (L x W x H) Space unit / mm	650 x 340 x 470
Weight / Kg	16,5

COOLMOBILE 220

ACCESSORIES	Artikelnummer
Connection line, 5mtr	56.220.005
Connection line, 10mtr	56.220.010
Connection line, 20mtr	56.220.020
Connection line, 30mtr	56.220.030



Connection line